



# مصنع رأس الخيمة

للمواد اللاصقة والعازلة ركام ش.ذ.م

## RAS AL KHAIMAH

ADHESIVE & WATERPROOF MATERIALS FACTORY RAKAM LLC



## TECHNICAL CATALOGUE



FLOORING  
& TILING



WATER  
PROOFING



BONDING  
AGENTS



SEALANTS  
& REPAIR  
MORTARS



SPECIALITY  
PRODUCTS





**RAKAM**

# TECHNICAL DATA SHEET

## 204 RAK GROUT WP

(WATERPROOF TILE GROUT)



**RAK GROUT WP** is cement based, polymer modified, specially used for grouting in wet and submerged conditions.

ADVANTAGES	APPLICATION	STORAGE														
<ul style="list-style-type: none"> <li>• Non-shrinking</li> <li>• Chemical Resistant</li> <li>• Water Resistant</li> <li>• Non Yellowing</li> </ul>	<p>As a general rule on a porous surface, allow 24 hours. for tiles to set prior to grouting.</p> <p>Ensure the gaps between the tiles are clean, dry and free of adhesive.</p> <p>Mix complete 10 kg bag of powder into 2-3 litres of water with a partial slow speed drill until lump free paste is obtained.</p> <p>Apply RAK Grout-WP to the spaces between tiles. with proper rubber float or sponge, ensuring the joints and edges are completely filled and compacted.</p> <p>Remove surplus grout with a damp cloth, wet the applied area with water after 24 hours,</p> <p>When the grout is dry, polish tiles with clean, dry and soft cloth,</p>	<p>Store in dry place below 30°C away from direct sunlight</p>														
USES		HEALTH AND SAFETY	<p>As with all chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles, should be worn (see packaging for specific instructions). Treat any splashes to the skin or eyes with fresh water immediately. Should any of the product be accidentally swallowed, do not induce vomiting but call for medical assistance immediately. Ensure the container is available for the medical attendant to examine any relevant instructions and contents details. Reseal all containers after use and ensure product is stored as instructed on the safety section of the labelling.</p>													
CHARACTERISTICS		<h3 style="background-color: #e0e0e0;">ORDERING GUIDE</h3> <table border="1"> <tr> <td>PRODUCT NO.</td> <td>204</td> </tr> <tr> <td>STANDARDS</td> <td>ANSI - A118.4 BS-5980 Class A Type1</td> </tr> <tr> <td>PACKAGING</td> <td>10 kg Bags</td> </tr> <tr> <td>COLOR</td> <td>Standard: White / Grey Colors available on request</td> </tr> </table>	PRODUCT NO.	204	STANDARDS	ANSI - A118.4 BS-5980 Class A Type1	PACKAGING	10 kg Bags	COLOR	Standard: White / Grey Colors available on request						
PRODUCT NO.			204													
STANDARDS	ANSI - A118.4 BS-5980 Class A Type1															
PACKAGING	10 kg Bags															
COLOR	Standard: White / Grey Colors available on request															
<table border="0"> <tr> <td>Working Time of Grout Paste</td> <td>100 minutes at 25°C dries to tack-free film.</td> </tr> <tr> <td>Comprehensive Strength 24 hours</td> <td>(EN-12808-3) 6 N / mm<sup>2</sup></td> </tr> <tr> <td>Day 28</td> <td>30 N / mmi</td> </tr> <tr> <td>Flextural Strength (EN-12808-3)</td> <td>28 Day 7 N 1 ma 2 impregnation</td> </tr> <tr> <td>Coverage</td> <td>1 kg. of mixed product willcover 12 running meters per kg 6 mm wide x 3 mm depth.</td> </tr> <tr> <td>Water Absorption (EN-12808-5)</td> <td>30 mins :&lt; 3g 301) rains 5g</td> </tr> <tr> <td>Flammability</td> <td>Non flammable</td> </tr> </table>	Working Time of Grout Paste	100 minutes at 25°C dries to tack-free film.	Comprehensive Strength 24 hours	(EN-12808-3) 6 N / mm <sup>2</sup>	Day 28	30 N / mmi	Flextural Strength (EN-12808-3)	28 Day 7 N 1 ma 2 impregnation	Coverage	1 kg. of mixed product willcover 12 running meters per kg 6 mm wide x 3 mm depth.	Water Absorption (EN-12808-5)	30 mins :< 3g 301) rains 5g	Flammability	Non flammable		
Working Time of Grout Paste	100 minutes at 25°C dries to tack-free film.															
Comprehensive Strength 24 hours	(EN-12808-3) 6 N / mm <sup>2</sup>															
Day 28	30 N / mmi															
Flextural Strength (EN-12808-3)	28 Day 7 N 1 ma 2 impregnation															
Coverage	1 kg. of mixed product willcover 12 running meters per kg 6 mm wide x 3 mm depth.															
Water Absorption (EN-12808-5)	30 mins :< 3g 301) rains 5g															
Flammability	Non flammable															





# RAKAM



P.O. BOX 11005, RAS AL KHAIMAH - U.A.E

+9717 266 8383 +9717 266 8853

sales@rakam.ae www.rakam.ae



HIGH  
QUALITY



FAST  
DELIVERY



BEST  
PRICES

## مصنع رأس الخيمة

للمواد اللاصقة والعازلة ركام ش.ذ.م.م

**RAS AL KHAIMAH**  
ADHESIVE & WATERPROOF MATERIALS FACTORY RAKAM LLC



FLOORING & TILING

WATER PROOFING

BONDING AGENTS

SEALANTS & MORTARS

SPECIALITY PRODUCTS