



مصنع رأس الخيمة

للمواد اللاصقة والعازلة ركام ش.ذ.م.م

RAS AL KHAIMAH

ADHESIVE & WATERPROOF MATERIALS FACTORY RAKAM LLC



TECHNICAL CATALOGUE



FLOORING
& TILING



WATER
PROOFING



BONDING
AGENTS



SEALANTS
& REPAIR
MORTARS



SPECIALITY
PRODUCTS



TECHNICAL DATA SHEET




RAKAM



401 RAK ACRYSEAL

(ACRYLIC SEALANT)

RAK ACRYSEAL is a permanent, flexible sealant for a wide variety of internal applications where low (+/-5%) movement is anticipated. Excellent adhesion to most substrates.

PROPERTIES	APPLICATION	ORDERING GUIDE
<p>RAK ACRYSEAL, Acrylic Flexible Filler is a non staining, sealant that resists cracking and gives a smooth finish that requires no sanding</p>	<ul style="list-style-type: none"> Reseal container for storage and re-use. Store away from extreme heat and cold. Joint sizes more than 20 mm wide or 10 mm deep must be filled with backing rod as a back-up filler. Do not use for below waterline applications. Do not use as a putty. Do not apply when temperature is below 7°C 	<p>PRODUCT NO. 401</p> <p>STANDARDS ASTM C733</p> <p>PACKAGING 5 / 20 kg Packs</p> <p>COLOR White / Grey</p>
<p>USES</p> <p>Ideal for caulking and sealing: Door and window frames •Skirting Boards • Floorboards •Walls •Ceilings •Plasterboards</p> <p>ADHERES TO:-</p> <ul style="list-style-type: none"> Brick • Concrete • Plastic • Ceramics Tiles 		<p>HEALTH AND SAFETY</p> <p>As with all chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles, should be worn (see packaging for specific instructions). Treat any splashes to the skin or eyes with fresh water immediately. Should any of the product be accidentally swallowed, do not induce vomiting but call for medical assistance immediately. Ensure the container is available for the medical attendant to examine any relevant instructions and contents details. Reseal all containers after use and ensure product is stored as instructed on the safety section of the labelling.</p>
<p>TYPICAL PROPERTIES</p> <p>Application temperature +7°C to 40°C Working time 10 to 20 minutes Complete drying time 36 hours (Depending upon the substrate)</p> <p>Percentage solids 78 +2% Specific gravity 1.56 Movement joint 10°A</p>		
<p>SURFACE PREPARATION</p> <p>Ensure gaps and cracks to be filled are dry and free of grease, dirt, dust and any loose material. Fill the seam with sample amount of filler. Can be over-painted approximately two hours after application.</p>		<p>CLEANING</p> <p>Clean tools with soap and water after use.</p>
		<p>SHELF LIFE</p> <p>Up to 8 months in unopened packs stored under 30°C. kept out of direct sunlight</p>
	<p>CAUTION</p> <p>Avoid contact with eyes and skin. Only use in well-ventilated areas. Keep out of reach of children.</p>	



RAKAM



P.O. BOX 11005, RAS AL KHAIMAH - U.A.E

+9717 266 8383 +9717 266 8853

sales@rakam.ae www.rakam.ae



HIGH
QUALITY



FAST
DELIVERY



BEST
PRICES

مصنع رأس الخيمة

للمواد اللاصقة والعازلة ركام ش.ذ.م.م

RAS AL KHAIMAH
ADHESIVE & WATERPROOF MATERIALS FACTORY RAKAM LLC



FLOORING & TILING

WATER PROOFING

BONDING AGENTS

SEALANTS & MORTARS

SPECIALITY PRODUCTS