

TECHNICAL DATA SHEET

STELLAR

ستيلار



RAKAM





المعلومات الفنية

TECHNICAL DATA SHEET

STELLAR LATEX SEALER

DESCRIPTION & FIELD OF APPLICATION

A high quality, general-purpose insulating priming sealer, specially formulated as primary coat for emulsion paint systems indoors & outdoors, to penetrate, seal and block the absorption of very porous surfaces and to bond the dust which can not be brushed away.

MAIN FEATURES

- Excellent bonding strength.
- High penetrating power.
- Saturates and reinforces the surface.
- Improves the spreading rate of the subsequently applied coat."

*** A second coat can be applied after two hours...**

PHYSICAL SPECIFICATION

- | | |
|------------------------|--|
| ■ Specific gravity | ■ Approx. 1.39 g/cc |
| ■ Solid by volume | ■ Approx. 29% |
| ■ Coverage rate | ■ 10-12 M ² /Liter |
| ■ Dry film thickness | ■ 20 Microns |
| ■ Shelf life | ■ 12 months |
| ■ Flash point | ■ Not applicable |
| ■ Finish | ■ Matt or Eggshell |
| ■ Drying time at 25 °C | ■ "Surface dry approx. 1 hour Hard dry approx. 2 hours" |

SURFACE PREPARATION

The surface should be sound, dry and clean, free from dirt, oil, grease, and loose paint, or powdery materials...

A- OLD PAINTED SURFACES

- 1- "Remove the old paint as much as possible.
- 2- Sand the entire surface and remove all the dust.
- 3- Wash down with Ammonia Water Solution.
- 4- Rinse with clean water and allow to dry.
- 5- Prime the surface to be painted with STELLAR Primer Sealer or STELLAR Latex Sealer.
- 6- Fill cracks and holes with STELLAR Wall Putty or STELLAR Acrylic Filler.
- 7- After drying, sand the putty and clean the surface once again.
- 8- Apply two coats of STELLAR Interior Emulsion."

B- NEW SURFACES

- 1- Sand the surface until completely smooth, remove all the dust.
- 2- Prime the surface to be painted with STELLAR Primer Sealer or STELLAR Latex Sealer.
- 3- Apply 1-2 Coats of STELLAR Wall Putty or STELLAR Acrylic Filler.
- 4- After drying, sand the putty and clean the surface.
- 5- Apply two coats of STELLAR Interior Emulsion.

INSTRUCTION FOR USE

Airless Spray Gun

- | | |
|--------------------------|-------|
| ■ Tools | Brush |
| ■ Type of thinner | Water |
| ■ Percentage of thinning | 5-10% |

Air spray gun

- | | |
|--------------------------|-------------------------|
| ■ Type of thinner | Clean Water |
| ■ Percentage of thinning | 10 – 15% max. by volume |
| ■ Nozzle orifice | 1.5 – 2.0 mm |
| ■ Output pressure | 2 – 3 bar |

Brush / Roller

- | | |
|--------------------------|-------------------------|
| ■ Type of thinner | Clean Water |
| ■ Percentage of thinning | 10 – 20% max. by volume |

SUBSEQUENT COATS

- STELLAR Gloss Emulsion
- STELLAR Vinyl Silk
- STELLAR Exterior Acrylic Emulsion
- STELLAR -Tex Fine
- STELLAR -Tex Medium
- STELLAR -Tex Coarse
- STELLAR – gravio tex"

COLOURS

White and Transparent

PACKING

18 Lt./drum , 4lt gallon

REMARKS

- Stir well before use...
- Avoid application below 5 °C or over 85% relative humidity.
- After using, clean the application tools immediately with water.
- Close container after use.
- Store in a cool and dry place.
- Keep out of reach of children.
- For more information, please do not hesitate to contact our Technical Department."

STELLAR

ستيلار



RAKAM

مصنع رأس الخيمة للمواد اللاصقة والعازلة ركام ش ذ م م
ص.ب : 11005 رأس الخيمة إ.ع.م، تليفون : ٢٦٦ ٨٣٨٣ +٩٧١ فاكس : ٢٦٦ ٨٨٥٣ +٩٧١
بريد إلكتروني : sales@rakam.ae موقع إلكتروني : www.rakam.ae

RAS AL KHAIMAH ADHESIVE & WATERPROOF MATERIALS FACTORY RAKAM LLC
P.O. Box 11005, Ras Al Khaimah - U.A.E, Tel +9717 266 8383, Fax +9717 266 8853,
E-mail: sales@rakam.ae, Web: www.rakam.ae